

Mobil Gargoyle Arctic SHC NH 68

Synthetic Lubricant for refrigeration compressor - Ammonia application

Product Description

Mobil Gargoyle Arctic SHC NH 68 is a fully synthetic lubricant, specifically designed to lubricate refrigeration compressors in high performance plants using ammonia as refrigerating fluid. Mobil Gargoyle Arctic SHC NH 68 is formulated from wax free, synthesized hydrocarbons polyalphaolefin (PAO) and synthetic Alkylbenzene base oils, which have demonstrated outstanding resistance to thermal/oxidative degradation. Even in the worst operating conditions, Mobil Gargoyle Arctic SHC NH 68 will perform against sludge and deposit building, hence avoiding or minimizing valve or filter plugging.

Features and Benefits

The Gargoyle Arctic SHC brand of lubricants are recognised and appreciated around the world for their innovation and outstanding performance. These molecular design PAO synthetic products, pioneered by our research scientists, symbolise the continuing commitment to using advanced technology to provide outstanding lubricant products.

Features	Advantages and Potential Benefits
Wax-free	Excellent low temperature fluidity, no waxy deposits and improved evaporator efficiency
Superior thermal/oxidative and chemical stability	Long oil life compared to mineral lubricant, inducing extended drain intervals and less routine maintenance. In turn reduction of maintenance costs
Good compatibility with seals previously used with mineral lubricant	Limited risk of oil leakage
Low volatility	Avoids viscosity build-up, reduced oil consumption

Application

Mobil Gargoyle Arctic SHC NH 68 is recommended for use in screw or reciprocating refrigeration compressors, in plants using ammonia as refrigerating fluid.

Mobil Gargoyle Arctic SHC NH 68 is compatible with mineral lubricants, however, in case of switch over, performances or benefits may be minimized, depending on the ratio of mineral oil remaining in the blend. In such case, a specific oil analysis follow up with control of filters should be handled in the following 6 months accordingly.

Specifications and Approvals

Mobil Gargoyle Arctic SHC NH 68 meets or exceeds the following industry and builder specifications

Johnson Control
York



Mobil Gargoyle Arctic SHCNH 68 meets or exceeds the following industry and builder specifications

GEA Matal Grasso

Typical Properties

Test Method	Mobil Gargoyle Arctic SHC NH 68
ISO VG	68
Viscosity ASTM D445	
cSt at 40°C	64
cSt at 100°C	8.5
Viscosity Index ASTM D2270	111
Specific Gravity (@15 °C, Kg/l) ASTM D1298	0.85
Flash Point, oC ASTM D93	211
Pour Point, oC ASTM D97	- 54
Color ASTM D1500	0.5
Copper Strip Corrosion, ASTM D 130, 3 h@ 100°C	1A
Water Content, ppm, ASTM D 1533	<100

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contract office, or via the Internet on <http://www.exxonmobil.com>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The ExxonMobil logotype, Mobil and Gargoyle SHC are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2007 Exxon Mobil Corporation. All rights reserved.